

Fax- Request

EUBA

Antriebstechnik Eller GmbH
Ruhrau 44
45279 Germany

Fax: +49/201/8531125


Company:
Street:
City:
Country:
Phone:
Fax:
Interlocutor:

Regulating power dynamical

Pull daN
Push daN
Static stress..... daN

Strokemm
Velocitymm/s

Fitting position



Operating frequency:s/h
Cyclic duration factor% ED

Type of mounting:

- | | | |
|---|---|---|
| <input type="checkbox"/> bracket | <input type="checkbox"/> pivot | <input type="checkbox"/> clevis and bolt |
| <input type="checkbox"/> cardan joint | <input type="checkbox"/> flange | <input type="checkbox"/> shackle toggle joint + bearing |
| <input type="checkbox"/> angle ball +socket joint | <input type="checkbox"/> special fixing (on detail) | |

Conditions of surroundings:

- dusty
 humid
 tropic
 sea surrounding

Installation:

- outdoors
 roofed over
 closed room
.....meter above sea level

Specification

- high rust protection
 special finish
 bellow

Connecting voltage: **1AC**VHz **DC**.....V
 3AC/.....VHz

Enclosure: IP-..... **Ambient temperature** +.....°C to -.....°C
Insulation class:

Way limit switch:

- | | |
|--|--|
| <input type="checkbox"/> 2 <input type="checkbox"/> 4 <input type="checkbox"/> 6 adjustable limit switches | <input type="checkbox"/> 1 or <input type="checkbox"/> 2 polar |
| <input type="checkbox"/> potentiometerOhm | <input type="checkbox"/> precision potentiometerOhm |
| <input type="checkbox"/> electronic position 4-20 mA transmitter | <input type="checkbox"/> special construction (on details) |

Special types:

- | | | |
|---|---|--|
| <input type="checkbox"/> PTC thermistor sensors | <input type="checkbox"/> brake motor | <input type="checkbox"/> motor stagnation heater |
| <input type="checkbox"/> plug connection | <input type="checkbox"/> switch box actuator-heater | |

In case these actuators are meant to be substitutes for old ones, please be so kind and send us these actuator numbers (you can find it on the nameplate of the actuator, or on our actuator itself.)